

# Spojnice za male i mikro cijevi





MS

- ✓ za FTTX
- ✓ mehanički konektori
- ✓ rastavljivi za različite uvjete okoline
- ✓ jednostavna montaža
- ✓ višestruka upotreba
- ✓ za velike radne pritiske
- ✓ prozirni (vidljiv prolaz kabela)



Za spajanje mikrocijevi koriste se mehaničke razdjelne spojnice u obliku konektora. U otežanim uvjetima, za uvod u zgrade i po katovima, koristimo opremu za blokiranje plina i vode. Spojna oprema je za cijevi  $\Phi 5$ ,  $\Phi 7$ ,  $\Phi 10$ ,  $\Phi 12$ ,  $\Phi 14$  i  $\Phi 16$ mm.

## Podaci za narudžbu i tehnički podaci

		kataloški broj	kod	vanjski promjer	pakiranje
	ravne spojnice		MS 05 MS 07 MS 10 MS 12 MS 14 MS 16	5 mm 7 mm 10 mm 12 mm 14 mm 16 mm	50 kom 50 kom 20 kom 20 kom 10 kom 10 kom
	krajnja spojnica / čep za pritisak		MSK 05 MSK 07 MSK 10 MSK 12 MSK 14 MSK 16	5 mm 7 mm 10 mm 12 mm 14 mm 16 mm	50 kom 50 kom 20 kom 20 kom 10 kom 10 kom
	redukcijska spojnica		MSK 510 MSK 710 MSK 1012 MSK 1214 MSK 1216 MSK 1416	5 – 10 mm 7 – 10 mm 10 – 12 mm 12 – 14 mm 12 – 16 mm 14 – 16 mm	10 kom
	ravna spojnica s plaštom		MSPL 10 MSPL 12 MSPL 14 MSPL 16	10 mm 12 mm 14 mm 16 mm	10 kom



Radni pritisak:  $\geq 15$  bara  
 Maksimalni kratkoročni pritisak: 25 bara  
 Maksimalna vučna sila:  $\geq 150$  N